



Usage & Features: Pricing Scale、Counting Scale

Specification

| Rated Capacities | 0.3,0.6,1.5,3(kg) |
|------------------------------|--|
| Rated Output | 0.9mV/V±10% |
| Zero Balance | ±0.045 mV/V |
| Non-linearity | 0.01 %R.O. |
| Hysteresis | 0.01 %R.O. |
| Repeatability | 0.02 %R.O. |
| 30mins Creep | 0.01 %R.O. |
| 30mins Return | 0.02 %R.O. |
| Safe Overload | 150 %R.O. |
| Ultimate Overload | 250 %R.O. |
| Temperature Effect On Output | 0.0040 %R.O°C./ |
| Temperature Effect On Zero | 0.0030 %R.O°C./ |
| Input Impedance | 415±15 Ω |
| Output Impedance | 350±3 Ω |
| Insulation Impedance | ≥2000Ω |
| Recommended Excitation | 10~15 VDC |
| Maximum Excitation | 15 VDC |
| Operating Temperature Range | -3~70°C |
| Construction | Aluminum Alloy |
| Protection Class | IP66 |
| Cable | φ4×0.5m |
| Recommended Platform Size | 200×200 mm |
| Mode of Connection | Red (EXC+) ,Black (EXC-) ,Green (SIG+) ,White (SIG-) |